

MITOYA RL-480 LED RING LAMP



User Manual

Kit contents:

- 1 × LED lamp RL-480
- 1 × AC adapter 18 V / 3 A
- 1 × Ball head for phone holder with ¼ inch male threads
- 1 × Phone holder with two ¼ inch female threads
- 1 × Bag

GEARING UP

- 1) Connect the lamp to the 18 V / 3 A AC adapter included in the kit.
- 2) Plug the AC adapter into a power outlet.
- 3) Turn on the lamp using the [ON/OFF | Dimmer] knob.

Remember the order of connecting the lamp first to the power supply, and then the power supply along with the lamp to the power outlet!

Maintaining the correct sequence will protect the lamp from accidental voltage spikes in the local network that could damage its electronics!

CHANGING LIGHT SETTINGS

The power of the lamp can be adjusted steplessly with the [ON/OFF | Dimmer] knob from 1% to 99%.

The color of the light, i.e. its color temperature, can be adjusted smoothly with the [COLOR TEMPERATURE] knob from 3000 to 6000 K.



MOUNTING THE LAMP ON A TRIPOD 16 mm

The RL-480 lamp has an integrated, articulated mounting bracket for a 16mm tripod head. The joint has two butterfly screws. The top screw allows the angle of the lamp to be changed. The bottom screw is used to clamp the lamp to the tripod head.

- 1) Remove the bottom screw slightly so that the space in the center of the mounting hole is empty.
- 2) Slide the lamp onto the 16mm tripod head.
- 3) Tighten the lower screw again until you feel resistance and the lamp is mounted firmly.

ATTENTION!

If you want to mount the lamp on a lighting tripod that has an additional ¼ inch thread, make sure that the thread is not protected by a black plastic nut. If the thread is protected by a nut, unscrew it and remove it before mounting the lamp - this will ensure greater stability of the lamp and safe operation.

MITOYA PENGUIN tripod is the only one with a horizontally or vertically repositionable head. If you are using the PENGUIN tripod flip the head to vertical before mounting the lamp!

PHONE HOLDER INSTALLATION

- 1) Screw the phone holder onto the male ¼ inch thread of the ball head using one of its two ¼ inch female holes.
- 2) Loosen the small screw at the top of the head to change the position of the phone holder and tighten it again to lock the holder in the new position.
- 3) The ball head is terminated at the bottom with a locking ring and a square foot - turn the locking ring upward.
- 4) Slide the head foot into one of the four profiled mounting holes in the lamp housing.
- 5) Turn the head's lock ring downward to clamp it firmly into the mounting hole.
- 6) Place the phone in the holder.

WARNINGS!

- Do not use a power supply other than the one included in the kit to power the lamp.
- Do not unplug the lamp during operation.
- Do not use the lamp in places with very high temperature and humidity.
- Do not cover the vents in the housing.
- When tilting the lamp forward 90°, always tilt it along one of the tripod legs to maintain a safe center of gravity for the set.

DISTRIBUTION AND CONTACT